## APPARATUS FOR THE DETERMINATION OF WATER SEPARABILITY OF PETROLEUM OILS AND SYNTHETIC FLUIDS ASTM D 1401 - ISO 6614

The apparatus consists of a steel frame supporting the control box, the jar and an electric lift that permits to move the stirrer blade up and down in the test cylinder. The speed of the stirrer is continuously showed on a digital tachometer.



- Borosilicate glass jar, 250 mm deep, mounted on a enamel finished benchtop steel frame.
- Anodized aluminium cover with six-position turntable for the insertion of the cylinders containing the samples: a positioning device permits to locate the cylinders exactly below the blade of the sample stirrer, avoiding breakings due to positioning mistakes.
- Electric lifting device for the stirrer support.
- Electric bath stirrer.
- Stainless steel heater.
- Electric sample stirrer.
- Digital tachometer which continuously shows the stirrer speed.
- Electronic timer which automatically stops the sample stirrer after 5 minutes stirring.
- Microprocessor controlled thermoregulator, PID action with builtin digital display 0.1 °C accuracy. Probe: PT100 RTD. Regulation accuracy ± 0.1 °C.
- Working range: from ambient to 100 ℃.
- Safety devices against overheating and low-level.
- Easy access control box placed on the right side of the apparatus containing all the electronics: anodized aluminium control panel with english written indications.
- English written user manual.
- For 220 V/50 Hz connections. Power consumption 800 W.
- Dimensions (I x w x h): mm 500 x 460 x 960 approx. Weight: kg 40 approx.
- CE marked.

AD1401-100 Apparatus

**ACCESSORIES** 

CAL001 PT100 simulator

CAL002 Officially certified PT100 simulator

**CONSUMABLES** 

AD1401-C00 Graduate cylinder, Pyrex glass TA009C-N00 ASTM 9C thermometer  $(-5\,^{\circ}\text{C}/+110\,^{\circ}\text{C})$  TA019C-N00 ASTM 19C thermometer  $(+49\,^{\circ}\text{C}/+57\,^{\circ}\text{C})$  ASTM 21C thermometer  $(+79\,^{\circ}\text{C}/+87\,^{\circ}\text{C})$ 

 $\underline{\underline{S}} pecifications \ may \ vary \ without \ notice.$ 

The apparatus is supplied bare without glassware (if any), accessories and consumables.



Agence Nord:

Plug N'Work - Campus Effiscience 2 Rue Jean Perrin - Bât D 14460 Colombelles

Agence Sud:

Tél: 02.31.34.50.74 Fax: 02.31.34.55.17

Hôtel d'Entreprises de La Croix Rouge - Lot A4

10 Av de la Croix Rouge - 84000 Avignon Tél : 04.90.27.17.95 Fax : 04.90.27.17.52 www.deltalabo.fr

