DIGITAL CONTACT ANGLE





laboratory balances



















laboratory electronic balances & oenological equipments

GIBERTINI ELETTRONICA SRL

Parc Club des Tanneries 2 Rue de la Faisanderie

DELTA LABO

67380 Lingolsheim tél : 03.88.04.01.81 fax: 03.68.93.01.52

> www.deltalabo.fr info@deltalabo.fr

ISO 9001:2008



LAT N° 094

Il Centro Accredia LAT n. 094 é accreditato per tarature di bilance, microdosatori e soluzioni idroalcoliche. Per i dettagli consultare la tabella di accreditamento su www.accredia.it ACCREDIA LAT Center n. 094 is accredited for balances, microdosimeters and hydroalcoholic solutions calibration. For details consult the accreditation table on www.accredia.it

www.gibertini.com





Agence Nord: Bâtiment LETNA

tél : 02.31.34.50.74

fax: 02.31.34.55.17

Boulevard de l'espérance 14123 Cormelles le Royal

Agence Sud: Bât Le Venango. 392 Rue Jean Dausset AGROPARC - BP11575 84916 Avignon Cédex 9

tél: 04.90.27.17.95 fax: 04.90.27.17.52

DIGITAL TENSIOMETER Mod. DCA

GENERAL FEATURES

- Display of surface tension value expressed in mN/m (dyne/cm) measured with the Wilhelmy method
- Precision: ± 0.02 mN/m (dyne/cm)
- Capacity: 1-1000 mN/m resolution 0.01 mN/m
- Max capacity: 110 g
- Autocalibration with internal mass
- Power source: 230 V -15% +10% by external power supply, 50 Hz
- Power consumption: 10 VA Dimensions: 210x370x380 mm.
- Weight: 8 Kg

EQUIPMENT

- Manual adjustable lab jack
- Thermometric probe PT 100 1/3 DIN:, temperature range: 0-50°C, Accuracy: ±0.05°C, Readability:
- Glass plates (dimensions 24×24×0.15 mm)
- Suspended system for the arrangement of glass plate
- Glass container for liquid sample

ACCESSORIES ON REQUEST

Platinum Wilhelmy plate Platinum Du Nouy ring

Floater calibrated in weight and in volume and double wall cylinder for density measurement:

- range of measure for the density: 0.5 ÷ 2.25 g/cm3
- readability: 0,00005 g/cm3
- reproducibility: ± 0,00005 g/cm3

Specific container for sample thermostatation

Special pan for metrological control