SMOKE POINT OF KEROSENE AND AVIATION TURBINE FUEL

Test Method

Smoke point is an indicator of the combustion qualities of aviation turbine fuels and kerosene. The fuel sample is burned in the Smoke Point Lamp, and the maximum flame height obtainable without smoking is measured.

Smoke Point Lamp

• Conforms to ASTM D1322 and related specifications

Burns fuel samples under controlled conditions for smoke point determinations of aviation turbine fuels and similar products. Consists of brass lamp body with chimney; gallery; 0-50mm black glass scale with white markings; brass plated door with curved glass window; candle socket; and plated brass candle with wick tube and air vent. Mounted on a cast iron base with aluminum support rod.

Ordering Information		
Catalog No.	Order (Qty
K27000	Smoke Point Lamp	1
	Accessories	
K27021	Extracted Cotton Wicks	
	Prepared in accordance with	
	ASTM D1322 (9.2) requirements.	
	Packed in a sealed tube with desiccant.	
	Case of 12	
K27020	Cotton Wicks, pack of 12	
K27050	Sighting Device	1
	Installs on chimney of Smoke Point Lamp.	
	Eliminates parallax	
K27060	Wick Insertion Tool	1
	Facilitates insertion of cotton wick into wick tube	
K27065	Wick Trimmer	1
	Use together with K27060 Insertion Tool	
	to place wick at the correct height in	
	the wick tube, free of twists and frayed ends.	
K27010	Interchangeable Candle	



Parc Club des Tanneries 2 Rue de la Faisanderie 67380 Lingolsheim tél: 03.88.04.01.81

fax: 03.68.93.01.52

www.deltalabo.fr info@deltalabo.fr



Specifications

Conforms to the specifications of: ASTM D1322; ISO 3014; IP 57; DIN 51406; FTM 791-2107; NF M 07-028

Included Accessories

Cotton Wicks, non-extracted (6) Interchangeable Candle

Dimensions dia.xh,in.(cm) 7x18½ (18x47) Net Weight: 10 lbs (4.5kg)

Shipping Information

Shipping Weight: 16 lbs (7.3kg) Dimensions: 5 Cu. ft.