

## Infracal 2 Biofuel Analyzers

MEASURING PERCENT BIODIESEL IN DIESEL  
OR ETHANOL IN GASOLINE



As more mandates for a minimum of ethanol in gasoline and biodiesel in diesel come into effect, a large number of major oil companies are blending higher percentages of biofuels at their terminals. Although manufacturers of in-line blending systems claim indisputable accuracy, a quick analytical measurement method to assess the blend ratio gives real data to a claimed assumption

In less than a minute, the user gets a direct readout in percent biodiesel or ethanol on-site at a terminal, distribution center or laboratory.

This can be a valuable asset for:

- Terminal managers
- Fuel distributors
- Engine manufacturers
- Fleet operators
- Regulatory agencies

Infracal 2 Biofuel Analyzers are:

- Rugged and compact
- Portable and easy to use
- Designed for non-technical personnel

The Infracal 2 Biofuel Analyzer is a low-cost, single wavelength analyzer with filters preset for a particular measurement – either biodiesel in diesel or ethanol in gasoline. Biodiesel has a characteristic infrared absorption band at  $5.73 \mu\text{m}$  ( $1745 \text{ cm}^{-1}$ ). Ethanol's infrared absorbance is at  $9.6 \mu\text{m}$  ( $1045 \text{ cm}^{-1}$ ). As the biodiesel or ethanol percentage increases, the infrared absorbance increases. An internal calibration table in the Infracal 2 Biofuel Analyzer converts infrared absorbance to a digital readout in percent. A fuel sample is placed directly on the exposed ATR sample window and after 10 seconds the percent biodiesel or percent ethanol is displayed. The fuel is easily cleaned off the window using a solvent and a wipe and the analyzer is ready for the next sample. The Infracal 2 Biofuel Analyzers are ideal where a single, repetitive analysis is needed.

**Infracal 2 ATR-B** for measuring percent biodiesel has a measurement range of 0-100% biodiesel in diesel and an accuracy of  $\pm 0.2$ , the Infracal 2 is based on proven IR technology developed by Wilks and used by regulatory agencies and fuel terminals worldwide. The compact, easy-to-use Infracal 2 ATR-B measurement results are comparable to both ASTM D7371 and EN 14078.

Biodiesel in diesel 0.2-30%  $\pm 0.2$   $\pm 0.2$

Biodiesel in diesel 30-100%  $\pm 1\%$  of concentration


**The Infracal 2 ATR-E** is the latest introduction to our easy to use analyzers for measuring ethanol in petrol. The Infracal 2 ATR-E is a stand-alone fixed filter infrared instrument that gives results that are comparable to gas chromatographic methods and correlates with ASTM 4815.

Ethanol in gasoline 0-20%  $\pm 0.2$

Ethanol in gasoline 70-98%  $\pm 1\%$  of concentration

### Principle of Operation

Samples are applied to a zinc selenide (ZnSe) attenuated total reflectance (ATR) sample plate. Infrared light from a source bounces multiple times between the top and bottom surfaces of ZnSe crystal as it travels horizontally from one side to the other. It is then filtered and measured by the detector. The loss of the light at a specific wavelength is due to the absorption by the fuel sample on the top plate and it is then calculated to percentage of biodiesel or ethanol based on calibration



## InfraCal 2 Biofuel Analyzers Ordering Information

PART NUMBERS		
405-2041-24	Model ATR-B calibrated: 0-100% biodiesel in diesel using standards prepared by a certified laboratory. Includes internal battery, auto adapter and universal power supply.	
405-2042-30	Model ATR-E calibrated: 0-20% & 70-100% ethanol in gasoline using standards prepared by a certified laboratory. Includes internal battery, auto adapter and universal power supply.	
SPECIFICATIONS		
	InfraCal 2 ATR-B	InfraCal 2 ATR-E
Applications	Biodiesel in diesel	Ethanol in gasoline
Analytical Wavelength/ Wave Number	5.7 mm, 1745 cm <sup>-1</sup>	9.6 mm, 1045 cm <sup>-1</sup>
Outputs	% (by weight) biodiesel in diesel	% (by weight) ethanol in gasoline
Analytical Range	0-100%	0-20 & 70-98%
Analysis Time	Less than 30 seconds	Less than 30 seconds
Instrument Repeatability	0-30% ± 0.2%, 20-100% ± 1% of biodiesel (FAME) concentration	0-20% ± 0.2%, 20-98% ± 1% of ethanol in petrol concentration
USER INTERFACE SPECIFICATIONS		
User Interface	6" color display	
Data input	Touch screen	
Communication Port	USB, RS 232	
POWER REQUIREMENTS		
Battery Power Source	18 volt NiCad battery	
External Power Requirements	18 volts DC, 3.3 amps	
Power Adaptor Input	Universal AC/DC	
Battery Run Time	4-6 hours	
OPERATING SPECIFICATIONS		
Sample Volume	< 1 ml	
Solvent/Reagent	None	
Operating Temperature	5°C - 40°C	
Relative Humidity	0-90%, non-condensing	
Altitude	Up to 5000 meters	

MECHANICAL SPECIFICATIONS	
Weight	7.0 lbs (3.2 kg)
Dimensions	6.7" x 7.8" x 5.2" (170 x 198 x 132 mm)
Shipping Weight	8.0 lbs (3.6 kg)
Shipping Dimensions	10 x 10 x 14" (254 x 254 x 355 mm)
COMPLIANCE	
CE, FCC Class B, NEMA 2, IP31	

INFRACAL 2 ATR-B CALIBRATION STANDARD SETS	
403-1050	<b>0-30% Biodiesel in Diesel Calibration Standards</b> The set includes eight standards; 0, 2, 5, 10, 15, 20, 25, and 30% biodiesel in High Cetane diesel fuel prepared by a certified laboratory. Each vial contains 20 ml of standard, good for a minimum of 15 tests.
403-1024	<b>0-100% Biodiesel in Diesel Calibration Standards</b> The set includes twelve standards; 0, 2, 5, 10, 15, 20, 25, 30, 50, 75, 95, 100 biodiesel in High Cetane diesel fuel prepared by a certified laboratory. Each vial contains 20 ml of standard, good for a minimum of 15 tests.

INFRACAL 2 ATR-E CALIBRATION STANDARD SETS	
403-1026	<b>5 Point Ethanol Low Concentration Calibration Standard Set</b> Standard concentrations are 0, 5, 10, 15, and 20% ethanol in gasoline. Standards are prepared by a certified laboratory. Each vial contains 20 ml of standard, good for a minimum of 15 tests.
403-1027	<b>5 Point Ethanol High Concentration Calibration Standard Set</b> Standard concentrations are 70, 80, 90, 95, and 100% ethanol in gasoline. Standards are prepared by a certified laboratory. Each vial contains 20 ml of standard, good for a minimum of 15 tests.

ACCESSORIES	
403-0013	Carrying case for InfraCal Analyzers with pre-diced pluck foam. 18.5" x 14.6" x 8"; 10 lbs
403-1086	Dust cover



**Agence Nord:**  
ZA Object'ifs Sud - Lot A3  
6 Allée Emilie du Châtelet  
14123 Ifs  
tél : 02.31.34.50.74  
fax : 02.31.34.55.17

**Agence Sud:**  
Bât Le Venango. 392 Rue Jean Dausset  
AGROPARC - BP11575  
84916 Avignon Cédex 9  
tél : 04.90.27.17.95 fax : 04.90.27.17.52



**Agence Est:**  
Parc Club des Tanneries  
2 Rue de la Faisanderie  
67380 Lingolsheim  
tél : 03.88.04.01.81  
fax : 03.68.93.01.52

[www.deltalabo.fr](http://www.deltalabo.fr)  
[info@deltalabo.fr](mailto:info@deltalabo.fr)

**Spectro Scientific** | One Executive Drive, Suite 101, Chelmsford, MA 01824-2563  
978-431-1120 | [www.spectrosci.com](http://www.spectrosci.com) | [sales@spectrosci.com](mailto:sales@spectrosci.com) | An ISO 9001:2008 company

Copyright © 2017 Spectro Scientific. All rights reserved. While every effort is made to assure the information in this document is accurate, Spectro Scientific does not accept liability for any errors or mistakes that may arise. Specifications are subject to change without notice. InfraCal 2 ATR-B & ATR-E\_DSv1\_2017-06-30